ENGINEERING CHANGE NOTICE

Page 1 of <u>2</u>

(mark one) Supplemental (Mark one) B. C. Simpson, LMHC, R2-12 Direct Revision (Mark one) Change ECN (I) Temporary (I) Standby (I) Tank 241-U-201 And Telephone No. B. C. Simpson, LMHC, R2-12 [] Yes [X] No 8-20-97 7. Bldg./Sys./Fac. No. 8. Approval D	
Change ECN [] 6. Project Title/No./Work Order No. 7. Bldg./Sys./Fac. No. 8. Approval D	i
	esignator
	[
Supersedure [] 9. Document Numbers Changed by this ECN 10. Related ECN No(s). 11. Related P	O No.
(includes sheet no. and rev.) WHC-SD-WM-ER-483, Rev. OB NA NA	
12a. Modification Work 12b. Work Package 12c. Modification Work Complete 12d. Restored to Original	
No. tion (Temp. or Standby ECN) Tion (Temp. or Standby ECN) NA	ionly)
L Yes (fill out Blk. NA NA NA NA NA NA	
[X] No (NA Blks. 12b, Design Authority/Cog. Engineer Design Authority/Cog. E 12c, 12d) Signature & Date Signature & Date	
13a. Description of Change 13b. Design Baseline Document? [] Yes [X] No Add Appendix B, Evaluation to Establish Best-Basis Inventory for Single-Shell Tan 241-U-201.	k
	1
·	
14a. Justification (mark one)	
Criteria Change $igl[]$ Design Improvement $igl[]$ Environmental $igl[]$ Facility Deactivation	
As-Found [X] Facilitate Const [] Const. Error/Omission [] Design Error/Omission	
14b. Justification Details An effort is underway to provide waste inventory estimates that will serve	30
standard characterization source terms for the various waste management activitie	
part of this effort, an evaluation of available information for single-shell tank	
241-U-201 was performed, and a best-basis inventory was established. This work f	ollows [
the methodology that was established by the standard inventory task.)
15. Distribution (include name, MSIN, and no. of copies) RELEASE STAMP	
Central Files A3-88 K. M. Hall R2-12 DOE Reading Room H2-53 K. M. Hodgson R2-11 TCSRC R1-10 R T Winward H5-49	
Tile UE 40 D.D. Schweiben D2 12	i [
R C Simpson R2-12	
M. J. Kupfer H5-49	3 ID:
M. D. LeClair (3) H0-50	20)

ENGINEERING CHANGE NOTICE					Page 2 of 2	1. ECN (use no. f	rom pg. 1)
16. Design Verification Required	17. Cost Impact ENGINE	ERING	cons	STRUCT	ION	18. Schedule Impact (days)
[] Yes	Additional	Γ1 \$.	Additional	Γ	1 \$	Improvement []	
[X] No	Savings	ři \$	Savings	Ī	1 \$	Delay []	
19. Change Impact R	eview: Indicate t	he related do	cuments (other than	n the	engineering d	ocuments identified on S	ide 1)
that will be af SDD/DD	fected by the char	ge described	in Block 13. Ente :/Stress Analysis	r the	affected docur	ment number in Block 20. Tank Calibration Manual	
Functional Design Criteria			Design Report		[]	Health Physics Procedure	
Operating Specification	' []·		e Control Drawing		[] []	Spares Multiple Unit Listing	[] [7
Criticality Specification	[]		ion Procedure		L J Г 7	Test Procedures/Specification	n []
Conceptual Design Repor	lj t []	Installa	tion Procedure		[] []	Component Index	[] []
Equipment Spec.	[]	Mainter	nance Procedure		[]	ASME Coded Item	[]
Const. Spec.	[]	Engine	ering Procedure		[]	Human Factor Consideration	[]
Procurement Spec.	[]	Operati	ng Instruction		ři .	Computer Software	[]
Vendor Information	įj	Operati	ng Procedure		ii	Electric Circuit Schedule	[]
OM Manual	· [j	Operati	onal Safety Requiremen	it	[]	ICRS Procedure	įį
FSAR/SAR	ĨĨ	IEFD Dr	awing		ĪĪ	Process Control Manual/Plan	<u>.</u> []
Safety Equipment List	ĨĨ	Cell Arr	angement Drawing		[]	Process Flow Chart	[]
Radiation Work Permit	[]	Essenti	al Material Specification	1	[]	Purchase Requisition	[]
Environmental Impact Sta	atement []	Fac. Pro	oc. Samp. Schedule		[]	Tickler File	[]
Environmental Report	[]		ion Plan		[]		[]
Environmental Permit	[]		ry Adjustment Request		[]		[]
indicate that t	Documents: (NOTE: he signing organiz mber/Revision	ation has beer	isted below will no n notified of other ocument Number/Rev	r affe	revised by the ected documents	is ECN.) Signatures bel s listed below. Document Number Revi:	
ŅA .	•						
	•						•
21. Approvals	41					•	
ZI. Approvata	Signature		Date		Sign	ature .	Date
Design Authority				Desig	n Agent		
Cog. Eng. M. J. Ku	pfer 200/5/4	sest_	020-7	PE		_	
Cog. Mgr. K. M. Ho	dgson K.M. Hodg		8-2497	QA			
QA ·	•			Safet	У		
Safety				Desig	n	-	•
Environ.	. 21 101	· 0	_ _	Envir	on.	, -	
Other R. D. Schrei	ber Kult DACI		8/25/94	Other		-	 _
				-		-	
			·	DEDVD	TMENT OF ENERG	,	
	-	-				rol Number that	
					s the Approval		
				455	****		
				ADDIT	IUNAL	,	
-						-	



Tank Characterization Report for Single-Shell Tank 241-U-201

B. C. Simpson (LMHC) and R. T. Winward (Meier Associates) Lockheed Martin Hanford Corporation, Richland, WA 99352 U.S. Department of Energy Contract DE-AC06-96RL13200

EDT/ECN: 634635

UC: 712

Org Code: 74610 B&R Code: EW3120074 Charge Code: N4G3A Total Pages: 83

_

Key Words: TCR, best-basis inventory

Abstract: An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities. As part of this effort, an evaluation of available information for single-shell tank 241-U-201 was performed, and a best-basis inventory was established. This work follows the methodology that was established by the standard inventory task.

TRADEMARK DISCLAIMER. Reference herein to any specific commercial product, process, or service by trade name, trademark, manufacturer, or otherwise, does not necessarily constitute or imply its endorsement, recommendation, or favoring by the United States Government or any agency thereof or its contractors or subcontractors.

Printed in the United States of America. To obtain copies of this document, contact: Document Control Services, P.O. Box 950, Mailstop H6-08, Richland WA 99352, Phone (509) 372-2420; Fax (509) 376-4989.

AUG 27 1997

DATE: MANFORD

STA: 37 RELEASE ID:

Acanis Bishop 8/27/97
Release Approval Date

Release Stamp

RECORD OF REVISION

(1) Document Number
WHC-SD-WM-ER-483

Page X

(2) Title

Tank Characterization Report for Single-Shell Tank 241-U-201

TOTAL CHE	21 UCL	erization Report for Single-Shell lank 241-U-		
		CHANGE CONTROL RECORD	Authori	zed for Release
(3) Revis	ion	(4) Description of Change - Replace, Add, and Delete Pages	(5) Cog. Engr.	(6) Cog. Mgr. Date
0		Initially released 08/07/95 on EDT-611432.	R.D. Schreiber	J.G. Kristofzski
0-A	RS	Incorporate per ECN-623849.	L.M. Sasaki Sm.Sasaki	J.G. Kristofzski
0-B	RS	Incorporate per ECN-625695.	S.E. Kelly	J.G. Kristofzski
00 1	RS	Incorporate per ECN-634635.	M.J. Kupfer 13/ベルタ 8-21×	K.M. Hodgson TK.M. Hodge 82497
			,	
	·			
,				

APPENDIX B

EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR SINGLE-SHELL TANK 241-U-201

This page intentionally left blank.

APPENDIX B

EVALUATION TO ESTABLISH BEST-BASIS INVENTORY FOR SINGLE-SHELL TANK 241-U-201

An effort is underway to provide waste inventory estimates that will serve as standard characterization source terms for the various waste management activities (Hodgson and LeClair 1996). As part of this effort, an evaluation of available information for single-shell tank 241-U-201 was performed, and a best-basis inventory was established. This work, detailed in the following sections, follows the methodology that was established by the standard inventory task.

B1.0 CHEMICAL INFORMATION SOURCES .

Available chemical information for tank 241-U-201 includes the following:

- Data from push mode cores taken in 1995 (Sathyanarayana 1995). Only safety screening analyses were performed, therefore, the only data pertinent to this assessment were the total alpha and percent water assays.
- Data from two push mode cores taken in 1995 from tank 241-U-204, a tank with a closely related process history (Raphael and Tran 1995)
- Data from other tanks containing reduction and oxidation (REDOX) process (R)/REDOX coating waste (CWR1) sludge, tanks 241-S-104 and 241-S-107 (DiCenso et al. 1994, Simpson et al. 1996).
- The inventory estimate for this tank generated from the Hanford Defined Waste (HDW) model (Agnew et al. 1997a).

B2.0 COMPARISON OF COMPONENT INVENTORY VALUES

No sample based inventory estimate is available for this tank. The HDW model estimates (Agnew et al. 1997a) for tank 241-U-201 are shown in Table B2-1 and B2-2. The chemical species are reported without charge designation per the best-basis inventory convention.

The HDW inventory estimates uses a solid waste volume of 15.1 kL (4 kgal), a supernatant volume of 3.8 kL (1 kgal), and an overall waste density of 1.62 g/mL. Note that the HDW model has been updated since the initial publication of this tank characterization report (TCR); therefore, many of the values cited from the current version of the HDW model are not consistent with the version cited in the body of this TCR.

The calculation of a separate supernatant contribution will be excluded in the development and comparison of data-based inventory estimates, because the inventory contributions from the supernatant (except for water) are typically within the calculated uncertainty. However, the total inventory estimate and volume (supernatant and sludge) will be used from the HDW as a basis for comparison.

Table B2-1. Hanford Defined Waste-Based Inventory Estimates for Nonradioactive Components in Tank 241-U-201.

Analyte	HDW ^a inventory estimate (kg)	Analyte	HDW ^a inventory estimate (kg)
Al	4,580	NO ₃	538
Bi	1.56 E-04	OH .	10,700
Ca	73.3	oxalate	0
Cl	3.80	Pb	369
Cr	1.62	P as PO ₄	3.42 E-03
F	6.85 E-04	Si	8.55
Fe	139	S as SO ₄	12.2
Hg	12.4	Sr	0
K	0.91	TIC as CO ₃	110
La	0	TOC	0
Mn	0	U_{TOTAL}	653
Na	2,730	Zr	5.66 E-06
NH ₃	0.0537	H ₂ O (wt%)	33.9
Ni	0.91	density (kg/L)	1.62
NO ₂	667		

HDW = Hanford Defined Waste

^a Agnew et al. (1997a).

Table B2-2. Hanford Defined Waste Predicted Inventory Estimates for Radioactive Components in Tank 241-U-201.

Analyte	HDW ^{a,b} inventory estimate (Ci)	Analyte	HDW ^{a,b} inventory estimate (Ci)
⁹⁰ Sr	31.1	²³⁹ Pu	24.3
¹³⁷ Cs	35.8	²⁴⁰ Pu	3.43

HDW = Hanford Defined Waste

B3.0 COMPONENT INVENTORY EVALUATION

The following evaluation of tank contents is performed in order to identify potential errors and/or missing information that would influence the sample-based and HDW model component inventories. The types and volumes of solids accumulated in tank 241-U-201 reported by various authors is compiled in Table B3-1.

B3.1 CONTRIBUTING WASTE TYPES

The process history documents indicate the tank received mostly cladding waste from REDOX (CWR1) while the tank was active. Tank 241-U-201 went into service in 1956 receiving CWR1 from tank 241-U-110 through a diversion box (Agnew et al. 1997b). Before receiving CWR1, approximately 4,500 kL (1,190 kgal) of REDOX high-level (R) waste had been transferred through tank 241-U-110. The waste transferred to tank 241-U-201 may have been a combination of CWR1 and R waste types. For the remainder of its service life, from 1956 to 1977, tank 241-U-201 stored CWR1 (Agnew et al. 1997b).

Agnew et al. (1997a): CWR1

Hill et al. (1995): CW

CWR1 = REDOX process cladding waste (aluminum clad fuel--1952 to 1960)

CW = cladding waste

Current surveillance data (Hanlon 1997) provides estimated volumes for these waste types. Agnew et al. (1997a) uses these values for bases as well. There has been no change, such as salt well pumping, to alter the volumes. These are the values in Table B3-1 used to derive inventories. The total volume is used in calculating inventories.

^a Agnew et al. (1997a)

^b The HDW model Rev. 4 reports inventories for 46 radionuclides. Only the four most significant are reported in this table. Radionuclides are decayed to January 1, 1994.

Table B3-1. Waste Volumes for Tank 241-U-201.

HDW ^a Volumes	kL	kgal	Surveillance volumes ^b	kL	kgal
CWR1	15.1	4	sludge	15.1	. 4
supernatant	3.8	1	supernatant	3.8	. 1
Total Tank	18.9	5	Total Tank	18.9	5

HDW = Hanford Defined Waste

B3.2 ASSUMPTIONS

The following evaluation provides an engineering assessment of tank 241-U-201 contents. For this evaluation, the following assumptions and observations are made:

- Tank waste mass is calculated using the measured average density from similar tanks (1.62 g/mL) and the solid tank volume listed in Hanlon (1997). The Agnew et al. (1997a) estimates have a different overall and sludge density basis (1.62 g/mL, and 1.77 g/mL, respectively).
- Only the CWR1 and R sludge waste streams contributed to solids formation.
- No comprehensive analytical data is available from tank 241-U-201.
- The sludge composition can be estimated by using sample-based concentrations from similar wastes (e.g., tanks 241-S-104, 241-S-107, and 241-U-204 [DiCenso et al. 1994, Simpson et al. 1996, and Raphael and Tran 1995]) for calculating the predicted engineering data set.
- No radiolysis of NO₃ to NO₂ is factored into this evaluation.

B3.3 BASIS FOR CALCULATIONS USED IN THIS ENGINEERING EVALUATION

The general approach in this engineering assessment is to identify waste types and their approximate volumes within the tank of interest. The sources of information may include analytical data from samples taken from the tank of interest, analytical data from other tanks thought to contain waste types similar to those thought to be in the tank of interest, and data from models utilizing historical process records. The confidence level assigned to the best-basis inventory values then depends on the level of agreement among the various

^a Agnew et al. (1997a)

^b Hanlon (1997).

information sources. This approach is best suited for cases where extensive analytical data exist from multiple sampling events from a number of tanks containing similar waste types.

The CWR1 sludge concentrations used in this engineering assessment were developed with analytical data taken from tanks 241-U-204, 241-S-104, and 241-S-107. Some REDOX process waste may be intermixed in tank 241-U-201. However, the same situation applies in the tanks used to predict the R1 waste concentration. Thus, the waste is considered a mixture. Data were selected based on Agnew et al. (1997a) predicted sludge location.

The concentrations from each tank and the segments used in the calculation are shown in Table B3-2. In many cases, data from several sources were assessed and used, some data sets were selected in favor of others (usually when evidence of bias or high variability was observed), and some of the average values include detection limit values, where additional data suggest the detection limits are high. The mean from each specified set of tank data was averaged to obtain the projected concentration for each analyte for the sludge. The HDW model values for CWR1 sludge are also listed in Table B3-2 for comparison with the data-derived values.

Table B3-2. Mean Sludge Composition Estimate for 241-U-200 Tanks (2 Sheets)

	Т	anks (segment	s)	Average	HDW model
Analyte	241-S-104* (all) (μg/g)	241-S-107 ^b (segments) (μg/g)	241-U-204° (average) (μg/g)	concentration ^d (µg/g)	CWR1 concentration ^ε (μg/g)
Al	117,000	56,400	221,000	132,000	171,000
В	26.6	49	<dl< td=""><td>38</td><td>NR</td></dl<>	38	NR
Bi	<45.7	NR	1,200	< 623	0
Ca	247	234	1,260	580	2,730
Cl	3,200	1,860	100	1,720	141
Cr	2,350	1,180	391	1,310	59.8
F	145	150	4,000	1,430	0
Fe	1,720	1,160	2,720	1,870	5,200
K	300	457	220	326	33.9
Mn	1,150	83	82	438	0
Na	121,000	60,400	18,200	66,500	102,000
Ni	56	206	3,940	1,400	33.7
NO ₂	25,900	34,300	3,000	21,100	24,900
NO ₃	191,000	57,600	12,000	86,900	20,000
Pb	29.6	33	7,300	2,450	13,800

Table B3-2. Mean Sludge Composition Estimate for 241-U-200 Tanks (2 Sheets)

	Т	anks (segment	s)	Average	HDW model	
Analyte	241-S-104 ^a (all) (μg/g)	241-S-107 ^b (segments) (μg/g)	241-U-204° (average) (μg/g)	concentration ^d (µg/g)	CWR1 concentration ^e (µg/g)	
PO ₄	<2,190	1,630	2,150	<1,990	0	
Si	1,330	1,060	2,390	1,590	319	
SO ₄	2,270	1,300	513	1,360	455	
Sr	424	378	33.9	279	0	
TOC	1,730	NR	471	1,100	0	
U	6,690	8,686	1,410	5,600	24,400	
Zn	20.1	24	902	315	NR	
Zr	33.6	131	26.4	63.7	0	
density	1.64	1.90	1.31	1.62	1.77	
Radionuclides ^f (μCi/g)						
¹³⁷ Cs	60.5	276	3.96	113	1.33	
⁹⁰ Sr	301	74	0.0092	125	1.16	
^{239/240} Pu	0.282	NR	0.097	0.19	1.04	

DL = Detection limit

HDW = Hanford Defined Waste

NR = Not reported

B3.4 INVENTORY COMPARISONS

Table B3-3 contains the total engineering assessment-based inventories calculated by developing the waste inventories using an average composition from tanks 241-S-104, 241-S-107, and 241-U-204 to produce the tank inventory as shown below. Calculations for Table B3-3 are: (average concentration of analyte in μ g/g) x (solid waste [4 kgal]) x 3,785 L/kgal x 1,000 mL/L x (density [1.62 g/mL]) x kg/(1 E+09) μ g = total kg for this waste type in the tank.

^a DiCenso et al. (1994)

^b Statistically determined median R1 sludge concentrations for tank 241-S-107 contained in attachment to Simpson et al. (1996)

[°] Raphael and Tran (1995)

d Average of analyte concentrations for tanks 241-S-104, 241-S-107, and 241-U-204

e Agnew et al. (1997a)

f Radionuclides decayed to January 1, 1994.

Table B3-3. Comparison of Hanford Defined Waste-Based and Data-Based Inventory Estimates for Tank 241-U-201.

Element	241-U-201	241-U-201
	HDW estimate ^a (kg)	Data-based estimate (kg)
Al	4,580	3,240
Bi	1.56 E-04	<15.3
Ca	73.3	14.2
Chloride	3.80	42.2
Cr	1.62	32.1
F	6.85 E-04	35.1
Fe	139	45.9
Pb .	369	60.0
Mn	0	10.7
Ni	0.91	34.3
NO ₃	538	2,130
NO ₂	667	518
PO ₄	3.42 E-03	<48.8
K	0.91	8.0
Si	8.55	40.0
Na	2,730	. 1,630
Sr	. 0	6.84
SO ₄	12.2	33.3
TOC	0	27.0
U	653	137
Zn	NR	7.72
Zr	5.66 E-06	1.56
Density (g/mL)	1.62	1.62
wt% H ₂ O	33.9	29.3
Radionuclides ^b (Ci)		
¹³⁷ Cs	35.8	2,770
⁹⁰ Sr	31.1	3,070
^{239/240} Pu	27.7	4.65

HDW = Hanford Defined Waste

^a Agnew et al. (1997a)
^b Radionuclides decayed to January 1, 1994.

B3.5 DOCUMENT ELEMENT BASIS

This section compares the sample-based estimate, the engineering assessment, and the inventory estimate calculated by the HDW model for selected analytes. Many of the differences observed between the estimates can be attributed to the differences in their respective mass bases. In other cases, the source term for the analyte in the waste type does not appear to be accurately described. Several analytes such as bismuth, nickel, manganese, phosphate, and TOC are not principal process chemicals in the CWR1 waste, but may be present in larger than expected amounts as a result of mixing with the first cycle bismuth phosphate process waste present in tank 241-U-110.

Aluminum. The two estimates are reasonably close. The data-based assessment is about 30 percent lower than the HDW estimate. They qualitatively agree that aluminum is a principal contributor to the waste in this tank. The difference in concentration between the HDW model and the average concentration based on other tanks is approximately 26 percent, accounting for most of the discrepancy. The data-based estimate may be biased low because of the acid-digestion result used from tank 241-S-107. The aluminum value from that tank could be much higher because of incomplete quantitation of the samples. However, given the assumptions of the HDW model and the measurement uncertainty, these values are in agreement.

Nitrate. The data-based assessment is about four times higher than the HDW estimate. They qualitatively agree that nitrate is a principal contributor to the waste in this tank. The source concentrations are approximately a factor of four different, accounting for nearly all of the discrepancy. Thus, there appears to be a source term error in the HDW model.

Nitrite. The two estimates are reasonably close. The data-based assessment is about 22 percent lower than the HDW estimate. They qualitatively agree that nitrite is a principal contributor to the waste in this tank. The source concentrations are approximately 17 percent different, accounting for much of the discrepancy. However, given the assumptions of the HDW model and the measurement uncertainty, these values are in agreement.

Sodium. The data-based assessment is 40 percent lower than the HDW estimate. They qualitatively agree that sodium is a principal contributor to the waste in this tank. The source concentrations are approximately a factor of two different, accounting for nearly all of the discrepancy. However the contributing waste data was highly variable, and significant differences were evident between the data from the two S Tank Farm tanks and tank 241-U-204. Thus, there may be a source term error in the HDW model, or the sample data available may not be representative of the waste in the tank.

Total Hydroxide. Once the best-basis inventories were determined, the hydroxide inventory was calculated by performing a charge balance with the valences of other analytes. In some cases, this approach requires that other analyte (e.g., sodium or nitrate) inventories be adjusted to achieve the charge balance. During such adjustments, the number of

significant figures is not increased. This charge balance approach is consistent with that used by Agnew et al. (1997a).

Water. The two estimates are reasonably close. They qualitatively agree that water is a principal contributor to the waste in this tank. Because of the volatility of water over time, the discrepancy observed is not unexpected.

B4.0 DEFINE THE BEST-BASIS AND ESTABLISH COMPONENT INVENTORIES

Information about chemical, radiological, and/or physical properties is used to perform safety analyses, engineering evaluations, and risk assessment associated with waste management activities, as well as regulatory issues. These activities include overseeing tank farm operations and identifying, monitoring, and resolving safety issues associated with these operations and with the tank wastes. Disposal activities involve designing equipment, processes, and facilities for retrieving wastes and processing them into a form that is suitable for long-term storage/disposal.

Chemical and radiological inventory information are generally derived using three approaches: (1) component inventories are estimated using results of sample analyses, (2) component inventories are estimated using the HDW model-based on process knowledge and historical information, or (3) a tank-specific process estimate is made based on process flowsheets, reactor fuel data, essential material usage, and other operating data. The information derived from these different approaches is often inconsistent

An evaluation of available chemical information for tank 241-U-201 was performed, including the following:

- An inventory estimate generated by the HDW model (Agnew et al. 1997a)
- A data-based inventory developed from concentration information from similar tanks.

Based on this evaluation, a best-basis inventory was developed for tank 241-U-201. No sampling information was available for tank 241-U-201; however, several tanks which were thought to contain similar wastes were used to derive an inventory. The data-based evaluation inventory was chosen as the best basis for those analytes for which sample-based analytical values were not available for the following reasons:

- No independent data sources are available to predict CWR1 compositions from process flowsheet or historical records.
- The data-based inventory estimates appear reasonable, given the process knowledge available.
- For those few analytes where no values were available from the data-based inventory, or the estimate was considered suspect, the HDW model values were used.

Best-basis tank inventory values are derived for 46 key radionuclides (as defined in Section 3.1 of Kupfer et al. 1997), all decayed to a common report date of January 1, 1994. Often, waste sample analyses have only reported 90Sr, 137Cs, 239/240Pu, and total uranium (or

total beta and total alpha), while other key radionuclides such as ⁶⁰Co, ⁹⁹Tc, ¹²⁹I, ¹⁵⁴Eu, ¹⁵⁵Eu, and ²⁴¹Am, etc., have been infrequently reported. For this reason it has been necessary to derive most of the 46 key radionuclides by computer models. These models estimate radionuclide activity in batches of reactor fuel, account for the split of radionuclides to various separations plant waste streams, and track their movement with tank waste transactions. (These computer models are described in Kupfer et al. 1997, Section 6.1 and in Watrous and Wootan 1997.) Model generated values for radionuclides in any of 177 tanks are reported in the HDW Rev. 4 model results (Agnew et al. 1997a). The best-basis value for any one analyte may be either a model result or a sample or engineering assessment-based result if available. (No attempt has been made to ratio or normalize model results for all 46 radionuclides when values for measured radionuclides disagree with the model.) For a discussion of typical error between model derived values and sample derived values, see Kupfer et al. 1997, Section 6.1.10.

The best-basis inventory for tank 241-U-201 is presented in Tables B4-1 and B4-2. The inventory values reported in Tables B4-1 and B4-2 are subject to change. Refer to the Tank Characterization Database (TCD) for the most current inventory values.

Table B4-1. Best-Basis Inventory Estimates for Nonradioactive Components in Tank 241-U-201 (Effective May 31, 1997).

		D-201 (Effective M	wy 51, 1227/1
Analyte	Total inventory (kg)	Basis (S, M, C or E) ¹	Comment
Al	3,240	E	
Bi	< 15.3	Е	
Ca	14.2	Е	
Cl	42.2	Е	·
TIC as CO ₃	110	M	
Cr	32.1	Е	
F	35.1	Е	
Fe	45.9	Е	
Hg	12.4	M	
K	8.0	Е	·
La	0	M	
Mn	10.7	Е	
Na	1,630	Е	
Ni	34.3	Е	
NO ₂	518	Е	
NO ₃	2,130	E	
OH _{TOTAL}	6,580	C	Derived from charge balance
Pb	60.0	E	
PO ₄	<48.8	E	
Si	40.0	Е	
SO ₄	33.3	Е	
Sr	6.84	E	
TOC	27.0	Е	·
U _{TOTAL}	137	E ·	,
Zr	1.56	Е	

¹S = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based

C = Calculated by charge balance; includes oxides as hydroxides, not including CO_3 , NO_2 , NO_3 , PO_4 , SO_4 , and SiO_3 .

Table B4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-U-201, Decayed to January 1, 1994 (Effective May 31, 1997). (2 Sheets)

	Total inventory	Basis	+ (Extension May 31, 1997). (2 Sheets)
Analyte	(Ci)	(S, M, or E) ¹	Comment
³ H	0.0155	M	
14C	0.00166	M	
⁵⁹ Ni	4.70 E-04	M	
⁶⁰ Co	7.18 E-04	M	
⁶³ Ni	0.0440	M	
⁷⁹ Se	3.62 E-04	M	
%Sr	3,070	E	
⁹⁰ Y	3,070	Е	Referenced to 90Sr
⁹³ Zr	0.00171	· M	
^{93m} Nb	0.00139	M	
⁹⁹ Tc	0.0119	M	
¹⁰⁶ Ru	4.19 E-09	M	
^{113m} Cd	0.00534	M	
¹²⁵ Sb	0.00120	M	
¹²⁶ Sn	5.51 E-04	M	
¹²⁹ I	2.29 E-05	M	
¹³⁴ Cs	2.52 E-05	M	
¹³⁷ Cs	2,770	Е	
^{137m} Ba	2,620	Е	Referenced to ¹³⁷ Cs
¹⁵¹ Sm	1.29	M	
¹⁵² Eu	0.00265	M	
¹⁵⁴ Eu	0.0175	M	
¹⁵⁵ Eu	0.126	M	
²²⁶ Ra	4.30 E-08	M	
²²⁷ Ac	2.21 E-07	M	
²²⁸ Ra	4.42 E-12	M	
²²⁹ Th	6.25 E-10	M	
²³¹ Pa	5.24 E-07	M	
²³² Th	6.14 E-13	M	
²³² U	9.79 E-06	M	
²³³ U	3.62 E-07	M	

Table B4-2. Best-Basis Inventory Estimates for Radioactive Components in Tank 241-U-201, Decayed to January 1, 1994 (Effective May 31, 1997). (2 Sheets)

	Total inventory	Basis	G
Analyte	(Ci)	(S, M, or E) ¹	Comment
²³⁴ U	0.224	М	
²³⁵ U	0.00952	M	
²³⁶ U	0.00493	M	
²³⁷ Np	8.35 E-05	M	
²³⁸ Pu	0.380	M	
²³⁸ U	0.218	M	
²³⁹ Pu	24.3	M	
²⁴⁰ Pu	3.43	M	
²⁴¹ Am	0.00623	· M	
²⁴¹ Pu	21.0	M	
²⁴² Cm	5.53 E-05	M	
²⁴² Pu	8.90 E-05	M	
²⁴³ Am	5.68 E-08	M	
²⁴³ Cm	1.26 E-06	M	
²⁴⁴ Cm	1.98 E-06	M	

 $^{^{1}}S$ = Sample-based

M = Hanford Defined Waste model-based, Agnew et al. (1997a)

E = Engineering assessment-based.

B5.0 APPENDIX B REFERENCES

- Agnew, S. F., J. Boyer, R. A. Corbin, T B. Duran, J. R. FitzPatrick, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997a, *Hanford Tank Chemical and Radionuclide Inventories: HDW Model Rev.* 4, LA-UR-96-3860, Los Alamos National Laboratory, Los Alamos, New Mexico.
- Agnew, S. F., R. A. Corbin, T. B. Duran, K. A. Jurgensen, T. P. Ortiz, and B. L. Young, 1997b, Waste Status and Transaction Record Summary (WSTRS Rev. 4), LA-UR-97-311 Rev. 0, Los Alamos National Laboratory, Los Alamos, New Mexico.
- DiCenso, A. T., L. C. Amato, J. D. Franklin, G. L. Nuttall, K. W. Johnson,
 P. Sathyanarayana, and B. C. Simpson, 1994, *Tank Characterization Report for Single-Shell Tank 241-S-104*, WHC-SD-WM-ER-370, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Hanlon, B. M., 1997, Waste Tank Summary Report for Month Ending March 31, 1996, HNF-EP-0182-108, Lockheed Martin Hanford Corporation, Richland, Washington.
- Hill, J. G., G. S. Anderson, and B. C. Simpson, 1995, The Sort on Radioactive Waste Type Model: A Method to Sort Single-Shell Tanks into Characteristic Groups, PNL-9814, Rev. 2, Pacific Northwest National Laboratory, Richland, Washington.
- Hodgson, K. M., and M. D. LeClair, 1996, Work Plan for Defining a Standard Inventory
 Estimate for Wastes Stored in Hanford Site Underground Tanks,
 WHC-SD-WM-WP-311, Rev. 1, Lockheed Martin Hanford Corporation, Richland,
 Washington.
- Kupfer, M. J., A. L. Boldt, B. A. Higley, K. M. Hodgson, L. W. Shelton, B. C. Simpson, and R. A. Watrous (LMHC), S. L. Lambert, and D. E. Place (SESC), R. M. Orme (NHC), G. L. Borsheim (Borsheim Associates), N. G. Colton (PNNL), M. D. LeClair (SAIC), R. T. Winward (Meier Associates), and W. W. Schulz (W²S Corporation), 1997, Standard Inventories of Chemicals and Radionuclides in Hanford Site Tank Wastes, HNF-SD-WM-TI-740, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.
- Sathyanarayana, P., 1995, 45-Day Safety Screening Results for Tank 241-U-201, Push Mode Cores 70, 73, and 74, WHC-SD-WM-DP-107, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Raphael, G. F., and T. T. Tran, 1995, *Tank Characterization Report for Single-Shell Tank* 241-U-204, WHC-SD-WM-ER-486, Rev. 0C, Westinghouse Hanford Company, Richland, Washington.

- Simpson, B. C., J. G. Field, D.W. Engel, and D. S. Daly, 1996, *Tank Characterization Report for Single-Shell Tank 241-S-107*, WHC-SD-WM-ER-589, Rev. 0, Westinghouse Hanford Company, Richland, Washington.
- Watrous, R. A., and D. W. Wootan, 1997, Activity of Fuel Batches Processed Through Hanford Separations Plants, 1944 Through 1989, HNF-SD-WM-TI-794, Rev. 0, Lockheed Martin Hanford Corporation, Richland, Washington.